



KEBEK®TIRE

KEBEK

QINGDAO KEBEK TIRE CO., LTD





QINGDAO KEBEK TIRE CO.,LTD

KEBEK[®]TIRE

www.chinakebektire.com

COMPANY PROFILE

Kebek Tire Co., Limited is one of the major tire manufacturers in China with a 18 years history of international cooperation and shared technologies since 1998.

It covers an area of over 93,000 square meters, which accounts for R&D department and 62,000 square meters of production plant.

Kebek Tire Co., Limited has an annual production capacity of more than 100,000 off-the-road tires, along with 8,000 giant off-the-road tires and 800,000 bias truck tires.

All the products reach all the internationally required manufacturing standards and quality control certifications including ISO 9001, DOT and the national CCC, etc.

Promotion gifts:





QINGDAO KEBEK TIRE CO.,LTD

KEBEK®TIRE

www.chinakebektire.com



R-1

**Traction pattern, suitably designed for on and off-the road use, in all weather condition

**Pattern are engineered to provide excellent traction to drive wheels

**Suitable for both implement and industrial/construction applications

SIZE	PR	Rim	Overall Diameter	Section Width	Tread Depth	Maximum Load		Inflation Pressure	TYPE
						drive wheel	steer wheel		
8-16	6	6LB	790	211	30	615		190	TT
11.2-28	6	W10	1205	285	35	1115		180	
11.2-28	8	W10	1205	285	35	1305		240	
12.4-24	6	W11	1159	315	44	1090		170	
12.4-24	8	W11	1159	315	44	1285		220	
12.4-28	6	W11	1260	315	36	1275		170	
12.4-28	8	W11	1260	315	36	1510		230	
16.9-30	10	W15L	1485	429	45	2240		190	
5.00-12	4	4.00E	590	145	24	280		200	
5.00-12	6	4.00E	590	145	24	315		275	
6.00-12	6	4.50E	640	165	24	335		180	
6.00-12	8	4.50E	640	165	24	405		250	
6.00-12	6	4.50E	640	165	24	335		180	
6.00-12	8	4.50E	640	165	24	405		250	
6.00-12	6	4.50E	640	165	24	335		180	
6.00-12	8	4.50E	640	165	24	405		250	
6.50-16	6	5.00F	765	180	25	565		250	
7.50-16	6	5.50F	810	205	26	650		210	
7.50-20	6	5.50F	910	205	26	760		210	
9.5-16	6	W8	860	240	33	800		210	
9.5-20	4	W8	950	240	33	640		140	
9.5-20	6	W8	950	240	33	810		210	
9.5-20	8	W8	950	240	33	955		280	
9.5-20	4	W8	950	240	33	640		140	
9.5-20	6	W8	950	240	33	810		210	
9.5-20	8	W8	950	240	33	955		280	
9.5-24	4	W8	1050	240	33	740		140	
9.5-24	6	W8	1050	240	33	940		210	
9.5-24	8	W8	1050	240	33	1110		280	
11.2-24	6	W10	1105	285	33	1045		180	TT/TL
11.2-24	8	W10	1105	285	33	1225		240	
8.3-20	10	W7	950	210	64	970		270	
8.3-24	10	W7	1050	210	64	1135		270	
11-32	12	W10	1460	305	90	1080		160	
13.6-24	12	W12	1210	345	90	1790		250	
14.9-24	12	W13	1265	378	90	1990		230	
14.9-26	12	W13	1315	378	90	2055		230	
14.9-30	12	W13	1415	378	95	2190		230	
16.9-34	12	W15L	1585	430	95	2605		200	
18.4-38	12	W16L	1755	467	95	3575		230	

Note: TT (Tyre+Tube) TL (Tubeless tyre)

More size coming soon...



QINGDAO KEBEK TIRE CO.,LTD

KEBEK®TIRE

www.chinakebektire.com

Radial Agr Tyre



- **Radial agriculture tyre with special strong carcass and 2.5 long working life
- **Radial structure tyre can be retread
- **Special compound meet European standard specially good for environment
- **Traction pattern, suitably designed for on and off-the road use, in all weather condition
- **Pattern are engineered to provide excellent traction to drive wheels

Size	Rim	Section Width (mm)	Overall Diameter (mm)	Pressure (Kpa)	Maximum Load Capacity (kg)	Type
380/85R28	13.0	389	1378	160	2060	TL
14.9R28						
420/85R28	13.0	452	1438	160	2430	
(16.9R28)						
420/85R30	15.0	458	1483	160	2500	
(16.9R30)						
420/85R34	15.0	439	1594	160	2650	
(16.9R34)						
460/85R30	16.0	488	1527	160	2900	
(18.4R30)						
460/85R34	16.0	491	1649	160	3075	
(18.4R34)						
460/85R38	16.0	482	1737	160	3250	
(18.4R38)						
520/85R38	18.0	546	1863	160	3875	
(20.8R38)						
520/85R42	16.0	560	1969	160	4125	
(20.8R42)						

Note: TL (Tubeless tyre)

R-2



- **Tread and sidewall rubber compounds fight off acid and ozone
- **Dual rubber compounds-flexible rubber on the sidewalls to resist weather cracking and checking
- **Plus super-tough rubber on the tread for long wear
- **Bolstered nose for long wear

SIZE	PR	Rim	Overall Diameter	Section Width	Maximum Load		Inflation Pressure	TYPE
					drive wheel	steer wheel		
6.00-16	4	4.50E	745	165	405		180	TT
6.00-16	6	4.50E	745	165	495		250	
19.5L-24	12	DW16	1340	535	2145		210	TT/TL
18.4-30	12	W16L	1550	467	3180		230	
28L-26	14	DW25	1615	715	4245		170	TT
14.9-24	8	W13	1305	378	1600		180	
14.9-28	8	W13	1406	378	1700		180	
18.4-34	10	W16L	1655	467	2725		180	
18.4-38	10	W16L	1755	467	2900		180	
23.1-26	12	DW20	1605	587	3250		170	
23.1-26	16	DW20	1605	587	3750		220	
23.1-30	12	DW20	1829	610	3450		170	
23.1-30	16	DW20	1829	610	4000		225	

Note: TT (Tyre+Tube) TL (Tubeless tyre)



QINGDAO KEBEK TIRE CO.,LTD

KEBEK®TIRE

www.chinakebektire.com

F-2



**Front tractor tire with wide three-rib design for most types of farming conditions

**Self-cleaning tread for positive steering

**Shock-fortified nylon-cord body resists impacts

**Specially fortified rubber resists stubble punctures and tyreerosion

SIZE	PR	Rim	Overall Diameter	Section Width	Tread Depth	Maximum drive wheel	Load steer wheel	Inflation Pressure	TYPE
4.00-14	4	3.00D	590	110	11	270		340	TT
4.00-14	6	3.00D	590	110	11	350		380	
5.00-15	4	4J	665	140	13	365		280	
5.00-15	6	4J	665	140	13	465		420	
5.00-15	8	4J	665	140	13	500		470	
5.50-16	6	4.00E	710	150	15	425		250	
5.50-16	10	4.00E	710	150	15	525		370	
7.50-16	4	5.50F	810	205	20	605		200	
7.50-16	6	5.50F	810	205	20	745		280	
7.50-16	10	5.50F	810	205	20	870		370	
6.50-20	4	5.00F	860	180	17.5	600		230	
6.50-20	6	5.00F	860	180	17.5	725		310	
6.50-20	8	5.00F	860	180	17.5	865		420	
9.00-16	10	6.00F	855	234	23	1250		390	
4.00-16	6	3.00D	640	110	13	420		380	
6.00-16	6	4.00E	739	159	10	515		360	
6.50-16	8	4.50E	761	173	14	560		330	TL
7.50-18	8	5.50F	860	205	20	945		375	
7.50-20	10	5.50F	928	215	16	1070		370	TT
9.5L-15	8	7.00	777	239	24	650		330	TT
11L-15	8	8.00	815	274	1	850		300	TT
10.00-16	8	W8L	894	274	16	1060		300	TL
11.00-16	8	W10L	967	315	16	1350		345	TL

Note: TT (Tyre+Tube) TL (Tubeless tyre)

F-3



**Optimum tread arc delivers fullest possible footprint

**Design for implement trailer;Motoagricola and multipurpose trucks etc

**Implement non-traction tyres with great transportation properties

SIZE	PR	Rim	Overall Diameter	Section Width	Tread Depth	Maximum drive wheel	Load steer wheel	Inflation Pressure	TYPE
10.0/80-12	6	9	710	264	9	1060		230	TL
10.0/80-12	8	9	710	264	9	1250		310	
10.0/80-12	10	9	710	264	9	1440		390	
10.5/80-18	10	W9	885	274	10	1360		370	
12.5/80-18	12	W9	965	308	10	1850		370	
10.0/75-15.3	6	9	760	264	9	1120		230	
10.0/75-15.3	8	9	760	264	9	1360		310	
10.0/75-15.3	10	9	760	264	9	1550		390	
10.0/75-15.3	12	9	760	264	9	1700		470	
10.0/75-15.3	14	9	760	264	10	1900		550	
10.0/75-15.3	16	9	760	264	10	2180		660	
10.0/75-15.3	18	9	760	264	10	2300		715	
10.0/75-15.3	22	9	760	264	10	2900		950	
11.5/80-15.3	8	9	845	290	10	1700		270	
11.5/80-15.3	10	9	845	290	10	1950		340	
11.5/80-15.3	12	9	845	290	10	2180		410	
11.5/80-15.3	14	9	845	290	10	2430		475	
11.5/80-15.3	16	9	845	290	10	2575		540	
11.5/80-15.3	18	9	845	290	10	2725		610	
13.0/65-18	16	11	890	336	10	2800		490	
12.5/80-15.3	14	9	889	307	11	2650		430	

Note: TL (Tubeless tyre)



QINGDAO KEBEK TIRE CO.,LTD

KEBEK®TIRE

www.chinakebektire.com

I-3

- **Large ground contact area for minimum soil compaction
- **Low ground pressure low rolling resistance on soft ground
- **Good lateral stability



Size	P.R.	T.D. mm	S.R.	O.D. mm	S.W. mm	Loading kg@		Pressure Kpa	Type
710/40-22.5	16	21	24.00	711	1153	40KM/h	50KM/h	170	TL
700/40-22.5	16			699	1145	4500	4125	170	
700/50-22.5	16			699	1270	5600	5000	180	
650/50-22.5	16			645	1224	4500	4125	200	
600/55-22.5	16		20.00	592	1229	5000	4500	200	
600/50-22.5	16			592	1172	5150	4625	260	
550/60-22.5	16			537	1252	4875	4390	280	
550/45-22.5	16		16.00	537	1086	4375	3940	280	
500/60-22.5	16			503	1191	4375	3940	300	
500/60-22.5	18					4875	4360	320	
500/45-22.5	16			503	1021	3350	3000	280	
400/55-22.5	16		13.00	403	1011	3075	2760	320	
385/65-22.5	18		11.75	388	1071	4500	4010	170	
360/60-22.5	12			364	1003	1750	1662	160	
500/50-17	14	18	13.00	500	933	2500	2246	360	
500/50-17	18					3450	3075	440	
400/60-15.5	14		13.00	404	868	2800	2500	360	
400/60-15.5	16					3250	2900	400	

Note: TL (Tubeless tyre)

R4

- **The SLR-4 tread and casing have been designed to offer maximum durability and traction specially
- **Extra heavy casing-Provides increased durability and provides extended service life
- **Stepped reinforced lugs-Provides excellent stability and self-cleaning



SIZE	PR	Rim	Overall Diameter	Section Width	Tread Depth	Maximum Load		Inflation Pressure	TYPE
10.5/80-18	10	W9	907	274	22	1360		370	TL
10.5/80-18	12	W9	907	274	22	1550		420	
12.5/80-18	12	W9	987	308	25	1850		370	
12.5/80-18	14	W9	987	308	25	2120		430	
19.5L-24	12	DW16A	1314	495	27	3450		230	
16.9-28	10	DW15L	1410	429	25	3250		260	
16.9-28	12	DW15L	1410	429	25	3450		260	
16.9-24	10	DW15L	1309	429	25	3250		260	

Note: TL (Tubeless tyre)

LS-2

- **Selected tubeless sizes for less expense and downtime
- **Upgrade to meet the demands of higher-horsepower machines and heavier loads
- **Heavy-duty bead-and-rim protector helps keep out debris
- **Compared to traction field & road



Size	P.R.	T.D. mm	S.R.	O.D. mm	S.W. mm	Pressure Kpa	Loading KG	Type
16.9-30LS	14	49	W15L	1510	430	280	3000	TT/TL
18.4-26LS	14	51	DW16	1475	467	170	2580	
18.4-30LS	12	51	DW16A	1575	467	210	3075	
18.4-34LS	12	51	W16L	1680	467	210	3250	
23.1-26LS	10	53	DW20	1630	587	140	3250	
24.5-32LS	12	54	DW21	1830	622	170	4495	
28L-26LS	14	57	DW25	1645	715	170	4285	
30.5L-32LS	16	55	DW27	1845	775	170	5370	

Note: TT (Tyre+Tube) TL (Tubeless tyre)



QINGDAO KEBEK TIRE CO.,LTD

KEBEK®TIRE

www.chinakebektire.com



A

B

C

Skid Steer Tyre

**Deep-tread tyre built especially for skid-steer and aerial lift equipment

**Heavy-duty sidewall and large curb rib deliver more stability and greater puncture resistance

**Built to last with deep tread, buttressed lugs, full sidewall protection and an aggressive rim deflector to keep put debris

**Special puncture-resistance rubber compounds take on the most demanding conditions

SIZE	PR	Rim	Overall Diameter	Section Width	Tread Depth	Maximum Load		Inflation Pressure	TYPE
						drive wheel	steer wheel		
10-16.5	10	8.25	773	264	19	2135		520	TL
12-16.5	12	9.75	831	307	19	2865		550	
14-17.5	14	10.5	921	349	19	3875		550	
15-19.5	14	11.75	1019	389	21	4565		485	
10-16.5	10	8.25	773	264	30	2135		520	
12-16.5	12	9.75	840	310	32	2865		550	



Solid Skid Steer Tyre

**Solid tyre with extra strong carcass

**Special compound with good abrasion resistance and cutting resistance

**Strong tyre with expecting life until finishing of the tread wear

**Suit to rough working conditions

Size	Rim	Diameter	Section Width	Weight	Load
		mm	mm	Kg	Kg
31*6*10	10-16.5	740	235	100.2	3415
33*6*11	12-16.5	838	276	125	4075
36*7*11	14-17.5	914	276	178	5650
40*9*13	15-19.5	1016	336	275	7545
38*7*13	16/70-20	960	330	208	6320



QINGDAO KEBEK TIRE CO.,LTD

KEBEK®TIRE

www.chinakebektire.com



PRESS-ON Solid Tyre

**Super lug wide and flat tread pattern makes tyres with high performance of stability

**Good design with low resistance for running

**Special compound with anti-wear resistance

Size		Load capacity(Kg)				
		Balance forklift				Other forklift
		10Km/h		16Km/h		
Inch	mm	Drive	Steer	Drive	Steer	16Km/h
10*5*61/4	254*127	1292	1156	1238	1142	993
10*5*61/2	254*127	1278	1142	1224	1129	986
101/2*6*5	267*152	1761	1564	1686	1564	1360
131/2*51/2*8	343*140	1904	1700	1822	1686	1469
14*5*10	356*127	1680	1518	1616	1506	1242
14*41/2*8	356*114*	1482	1319	1414	1306	1142
15*5*111/4	381*127	3415	3585	2905	3075	2390
15*6*111/4	381*152	3875	3955	3305	3420	2720
15*7*111/4	381*176	4325	4335	3715	3755	3040
15*8*111/4	381*203	4775	4560	4125	4090	3360
151/2*5*10	394*127	1470	1210	1315	1100	1050
151/2*6*10	394*152	1870	1530	1665	1400	1330
16*41/2*12	406*127	1890	1660	1742	1560	1400
16*5*101/2	406*127	1400	1250	1340	1240	1080
16*6*101/2	406*152	1780	1580	1700	1570	1370
16*7*101/2	406*178	2325	1910	2070	1740	1660
161/4*5*111/4	413*127	1530	1250	1360	1145	1090
161/4*6*111/4	413*152	1920	1580	1715	1440	1370
18*5*121/8	457*127	2081	1850	1986	1836	1591
18*6*121/8	457*152	2652	2366	2530	2339	2040
18*7*121/8	457*178	3223	2870	3087	2856	2475
18*8*121/8	457*203	2790	2480	2670	2470	2150
18*9*121/8	457*229	4372	3890	4175	3862	3359
21*7*15	533*178	2670	2380	2550	2360	2050
21*8*15	533*203	4270	3801	4080	3781	3291
21*9*15	533*229	4923	4379	1706	4352	3794
22*7*16	559*178	2975	2450	2650	2230	2125
22*8*19	559*203	4434	3944	4230	3917	3407
22*9*16	559*229	5100	4542	4882	4515	3930
22*10*16	559*254	5780	5141	5522	5114	4447
22*12*16	559*305	7120	6338	6800	6297	5481
28*12*22	711*305*	8527	7589	8146	7548	6562



Forklift Tyre

**Deep lug pattern suit to all kinds of tough road

**Special compound with good abrasion resistance, heat resistance and cutting resistance

Size	Ply	Overall Diameter (mm)	Section Width (mm)	Rim	Load Capacity (kgs)	Inflation Pressure (Kpa)	Pattern Depth (mm)	Type
5.00-8	10	468	144	3.50D	925	650	7.5	TT
6.00-9	10	540	166	4.00E	1250	850	9.5	
6.50-10	10	590	186	5.00F	1365	755	10	
7.00-9	12	585	190	5.00S	1650	850	11.5	
7.00-12	12	676	197	5.00S	2555	850	13.5	
8.25-12	12	765	235	6.5	2000	700	12	
8.25-15	14	830	250	6.5	3775	830	18.5	
28*9-15	14	706	231	7	3050	970	12	
18*7-8	14	443	157	4.33	1280	900	10	

Note: TT (Tyre+Tube)



QINGDAO KEBEK TIRE CO.,LTD

KEBEK®TIRE

www.chinakebektire.com



ST-602



ST-603



ST-604



ST-605

**Solid tyre with extra strong carcass

**Deep lug pattern suit to all kinds of tough road

**Solid tyre with maintenance free and warranty of 3 years

Size	Rim	Overall Diameter	Section Width	Load capacity(kg)						Other forklift	Pattern
				Balance forklift							
				10km/h		16km/h		26km/h			
				mm	mm	Drive	Steer	Drive	Steer	Drive	
15×4 1/2-8	3	371	108	905	725	675	655	805	605	625	ST602
5.00-8	3	458	127	1210	970	1175	880	1095	820	840	ST602
18×7-8	4.33	443	157	2350	1880	2265	1700	2110	1585	1620	ST602
6.00-9	4	521	145	1920	1535	1855	1390	1730	1295	1325	ST602
6.50-10	5	565	155	2840	2110	2545	1910	2370	1780	1820	ST602
7.00-9	5	550	159	2370	2015	2805	1925	2370	1750	1785	ST602
7.00-12	5	655	161	3015	2410	2910	2185	2710	2035	2075	ST602
8.25-15	6.5	805	207	4940	3950	4765	3575	4440	3330	3045	ST602
8.25-12	6.5	695	192	3326	2660	3215	2410	2995	2245	2295	ST602
8.15-15 (28×9-15)	7	710	209	4090	3270	3945	2960	3675	2755	2820	ST602
21×8-9	6	507	184	2810	2250	2715	2035	2530	1895	1940	ST604
23×9-10	6.5	575	193	4005	3205	3845	2885	3605	2705	2765	ST604
27×10-12	8	655	235	4465	3570	4315	3235	4020	3015	3080	ST604
20.5/70-16(big)	9.5	910	336								ST603
8.25-16	6.5	820	216								ST603
14/90-16	10	878	275	5965	4725			5625	4470		ST605
16/70-20	13	1002	393	9445	6655			8600	6700		ST605
20.5/70-16(small)		890	285								ST605



QINGDAO KEBEK TIRE CO.,LTD

KEBEK®TIRE

www.chinakebektire.com



ST-601

- **Solid tyre with extra strong carcass
- **Deep lug pattern suit to all kinds of tough road
- **Solid tyre with maintenance free and warranty of 3 years

Size	Rim	Overall Diameter	Section Width	Load capacity(kg)						Other forklift
				Balance forklift						
		mm	mm	10km/h		16km/h		26km/h		16km/h
				Drive	Steer	Drive	Steer	Drive	Steer	
3.00-5	2.15	245	73	450	340	/	/	370	270	/
3.20-8	3	320	100	470	360	/	/	390	300	/
4.00-8	3	404	113	1055	845	1020	765	950	715	730
4.50-12	3	553	120	1440	1150	/	/	1300	980	/
4.50-12	3.5	553	120	1440	1150	/	/	1300	980	/
5.00-8	3	458	127	1210	970	1175	880	1095	820	840
5.50-15	4.50E	676	144	2525	1870	/	/	2195	1625	/
16x6-8	4.33	399	147	1500	1200	1445	1085	1345	1010	1035
18x7-8	4.33	443	157	2350	1880	2265	1700	2110	1585	1620
21x8-9	6	507	184	2810	2250	2715	2035	2530	1895	1940
23x9-10	6.5	575	193	4005	3205	3845	2885	3605	2705	2765
23x10-12	8.00	585	229	3980	3420	3820	3210	3586	3010	2980
6.00-9	4	521	145	1920	1535	1855	1390	1730	1295	1325
6.50-10	5	565	155	2840	2110	2545	1910	2370	1780	1820
200/50-10	6.5	447	198	2370	1900	2290	1720	2135	1605	1630
7.00-9	5	550	159	2370	2015	2805	1925	2370	1750	1785
7.00-12	5	655	161	3015	2410	2910	2185	2710	2035	2075
7.00-15	5.5	740	180	3590	2870	3465	2600	3225	2420	2475
	6									
7.00-16	5.50F	819	181	3910	3130	3465	2600	3520	2640	2475
7.50-15	5.5	740	180	3690	2950	3425	2570	3190	2395	2450
7.50-15	6	740	180	3690	2950	3425	2570	3190	2395	2450
7.50-16	5.5	785	189	3910	3130	3780	2835	3520	2640	2700
	6									
	6.5									
8.25-15	6.5	805	207	4940	3950	4765	3575	4440	3330	3045
8.25-12	6.5	695	192	3326	2660	3215	2410	2995	2245	2295
8.15-15 (28"-15)	7	710	209	4090	3270	3945	2960	3675	2755	2820
8.25-20	6.5	925	212	5425	4340	5420	3930	4880	3735	3475
	7									
7.50-20	6.5	935	218	5165	4130	4985	3740	4640	3480	3560
250-15	7.5	680	230	4366	3400	4220	3160	3930	2955	3010
9.00-16	6.5	845	219	5135	4110	4965	3725	4625	3470	3550
300-15	8	780	241	5990	4700	5780	4335	5380	4037	4130
355/65-15	9.75	384	301	7120	5700	/	/	6410	4820	/
28x12.5-15	9.75	706	300	5735	4590	5540	4165	5170	3890	3955
32x12.1-15	9.75	823	301	7120	6700	5860	6170	6410	4520	4910
9.00-20	6.5	935	222	6450	5160	6235	4675	5805	4355	4450
	7									
10.00-20	7.5	1003	266	7240	5795	6995	5240	6610	4885	4995
	8									
11.00-20	8	1003	266	7560	6050	7300	5490	6810	5120	5210
12.00-20	8	1008	283	8800	7000	8500	6925	8000	6450	6595
	8.5									
12.00-24	8.5	1247	309	9575	7655	/	/	8600	6450	/
10.00-16	6.5	884	218	5135	4110	/	/	4625	3470	/
11.00-16	6.5	884	218	5135	4110	/	/	4625	3470	/
12.00-16	8	850	255	5135	4110	/	/	4625	3470	/
6.50-16	5.5	715	145	3425	2740	/	/	3080	2310	/



Excavator Tyre

- **Suitable for part off-road vehicles operating on sand ground and loose road surface
- **With stable ride, good floating force and steering ability
- **Extremely strong traction, good self-cleaning and wide tread pattern provides good floating

SIZE	PR	Rim	Overall Diameter	Section Width	Tread Depth	Maximum Load		Inflation Pressure	TYPE
						drive wheel	steer wheel		
8.25-20	14	6.5	992	245	19	2060		675	TT
9.00-20	14	7	1030	260	20	2500		700	
10.00-20	16	7.5	1062	280	20	3000		750	
11.00-20	16	8	1095	293	24	3200		725	

Note: TT (Tyre+Tube)



QINGDAO KEBEK TIRE CO.,LTD

KEBEK®TIRE

www.chinakebektire.com



A

B

Solid OTR Tyre

- **Solid tyre with extra strong carcass specially good for all kinds of rough road
- **Special compound with good abrasion resistance and cutting resistance
- **Strong tyre with expecting life until finishing of the tread wear
- **Suit for port and rough working conditions

Size	Pattern	Rim	OD(mm)	Width(mm)	10km/h		16km/h		26km/h	
					Load	Rotation	Load	Rotation	Load	Rotation
16.00-25	ST-606	11.25/2.0	1446	390	16860	13490	15170	11400	13480	10130
17.5-25	ST-606	14.00/1.5	1310	396	13000	10500	11000	8000	8500	7000
18.00-25	ST-606	13.00	1620	480	21000	16500	19500	13600	13500	13000
20.5-25	ST-606	17.00	1350	485	15000	11000	13000	8560	10000	7500
23.5-25	ST-606	19.50/2.5	1540	527	19500	14500	17000	13000	13500	11500
26.5-25	New-ST-606	22.00	1736	650	39300	31400	37400	28100	35400	26600
29.5-25	New-ST-606	22.00	1950	740	59100	48300	57800	43200	57300	41700



RIB/LUG Truck Tyre

- **Suitable for driving on highway and generally paved road
- **The unique pattern design and formula design, high quality raw material support
- **Has the overload, high-speed, and abrasion performance etc
- **Particular suits for long-distance truck vehicles

SIZE	PR	Rim	Overall Diameter	Section Width	Tread Depth	Maximum Load		Inflation Pressure
						drive wheel	steer wheel	
4.00-12	8	2.50C	517	105	7	290		250
4.50-12	6	3.00B	545	127	7	355		300
4.50-12	8	3.00B	545	127	7	412		400
5.00-12	6	3.50B	568	143	7	425		300
5.00-12	8	3.50B	568	143	7	487		400
12.00-20	18	8.5	315	1125	16	3750		3350
11.00-20	16	8.0	293	1085	16	3350		2900
10.00-20	16	7.5	278	1055	15	3000		2650
9.00-20	16	7.5	259	1018	15	2575		2255
8.25-20	14	6.5	235	974	14	2205		1940
7.50-20	14	6.0	215	935	14	1885		1655
7.00-20	12	5.5	200	904	12	1580		1385
9.00-16	14	6.50H	255	890	16	1955		1720
8.25-16	14	6.50H	235	855	14	1705		1500
7.50-16	14	6.00G	215	805	11	1500		1320
7.00-16	12	5.50F	200	775	11	1220		1075
6.50-16	10	5.50F	185	750	10	975		860
7.00-15	10	5.50F	200	750	11	1040		915
6.50-15	10	4.50E	180	730	10	950		825
6.50-14	10	4.50J	180	705	10	900		800
6.00-15	8	4.50E	170	705	11.5	720		630
6.00-14	8	4.50J	170	680	11.5	685		600
6.00-13	8	4.50J	170	655	11.5	655		570
5.00-14	8	3.00D	130	625	7	420		420



QINGDAO KEBEK TIRE CO.,LTD

KEBEK®TIRE

www.chinakebektire.com

Tyre designs for scrapers and heavy-duty trucks operating on relatively harsh road conditions in areas like mining area, tunnel and quarry, construction site etc.

Tyre characteristics: pattern with wide riding area provide good cutting and heating resistance.



E4



Loaders



Dozers

Size	PR	Standard Rim	Tread Depth	Tyre inflated dimension (mm)		Load Capacity (kg)		Pressure (kpa)	
				Section Width	Overall Diameter	10km/h	50km/h	10km/h	50km/h
18.00-25	36	13.00-2.5	53.5	495	1673	16000	9250	850	625
18.00-33	36	13.00-2.5	53.5	495	1877	18500	10600	850	625
21.00-35	40	15.00-3.0	53.5	575	2005	24300	14000	825	625
24.00-35	42	17.00-3.5	57	650	2178	29000	16500	750	550
24.00-49	48	17.00/3.5	63	653	2531	/	21800	/	650
27.00-49	48	19.50-4.0	63.5	735	2703	43700	25000	775	575
30.00-51	52	22.00-4.5	69.5	823	2904	53000	30000	750	550
33.00-51	58	24.00-5.0	75	894	3061	61500	35500	750	575
33.25-29	40	27.00-3.5	64	866	5151	25700	17000	525	400
36.00-51	58	26.00-5.0	82	988	3233	71000	41250	675	525
37.00-57	68	27.00-6.0	82	1016	3442	82500	51500	575	525
40.00-57	68	29.00-6.0	82	1097	3594	92500	54500	725	550
53/80-63	78	36.00-6.0	97	1531	3759	/	92500	/	700

The extra deep pattern is especially designed for loader with driving surface, unique cutting resistance, wear resistance.

It has longer service life and applicable for rough roads.




L5



Loaders



Dozers



Graders



SHUTTLE TRUCKS UNDERGROUND

Size	PR	Standard Rim	Tread Depth	Tyre inflated dimension (mm)		Load Capacity (kg)		Pressure (kpa)	
			(mm)	Section Width	Overall Diameter	10km/h	50km/h	10km/h	50km/h
17.5-25	20	14.00-1.5	63	445	1450	8250	5000	575	400
20.5-25	24	17.00-2.0	71	535	1536	10300	6700	525	400
23.5-25	24	19.50-2.5	78	595	1672	12500	8000	475	355
26.5-25	40	22.00-3.0	87	680	1820	20000	13600	700	575
29.5-25	40	25.00-3.5	101.5	825	2073	23600	15000	625	475
35/65-33	42	28.00-3.5	98	861	2088	26000	16400	625	450
45/65-45	46	36.00-4.5	117	1102	2723	43750	/	525	/
50/80-57	68	36.00-6.0	97	1257	3550	90000	/	625	/
52/80-57	68	36.00-6.0	97	1305	3619	92500	/	700	/



QINGDAO KEBEK TIRE CO.,LTD

KEBEK®TIRE

www.chinakebektire.com



E3/L3



Loaders



Dozers

*Tyre designs suitable for bulldozers, loaders and excavators operating under many conditions.
Tyre characteristics: conventional tread design, high strong carcass structure design provide
excellent anti-cutting heat and wear resistance, and excellent traction.*

Size	PR	Standard Rim	Tread Depth	Tyre inflated dimension (mm)		Load Capacity (kg)		Pressure (kpa)	
			(mm)	Section Width	Overall Diameter	10km/h	50km/h	10km/h	50km/h
14.00-24	24	10.00	25	376	1370	9500	5150	850	575
	28	10.00	25	376	1370	10000	5600	925	650
14.00-25	20	10.00	25	381	1384	8500	4625	700	475
	24	10.00	25	381	1384	9500	5000	850	575
16.00-24	28	10.00	25	381	1384	10000	5600	925	650
	32	11.25-2.0	25	430	1490	12500	7300	875	650
16.00-25	36	11.25-2.0	25	430	1490	13600	7750	975	725
	28	11.25-2.0	30	430	1490	11500	6700	750	575
17.5-25	16	14.00-1.5	26	445	1348	7300	4250	475	300
	20	14.00-1.5	26	445	1348	8250	5000	575	400
20.5-25	20	17.00-2.0	26	521	1493	9500	6000	450	325
23.5-25	20	19.50-2.5	30	597	1617	9500	6150	375	300
	24	19.50-2.5	30	597	1617	10900	7300	475	350
26.5-25	28	22.00-3.0	35	673	1750	15500	10000	475	350
29.5-25	28	25.00-3.5	35	749	1874	17500	11500	425	325
29.5-29	28	25.00-3.5	35	749	1975	19000	12150	425	325
18.00-25	32	13.00-2.5	30	495	1615	15000	8750	750	575
	36	13.00-2.5	30	495	1615	16000	9250	850	625
37.25-35	42	31.00-4.0	48	985	2385	33500	21800	525	400
37.50-39	44	32.00-4.5	46.5	985	2561	37500	24300	550	400
33.25-35	38	27.00-3.5	42.5	845	2240	28000	17000 18000	550	400
33.50-33	38	28.00-4.0	43	899	2215	29000	18500	550	400



SKID STEER



Bobcat mini loader

*Application to tractors operated in cane, rice, muddy and wet field farming.
Deep pattern provides powerful traction and self-cleaning ability.
Good design for long-wearing, tear-resistance and cracking resistance.*

Size	P.R	Rim	Overall Diameter (mm)	Section Width (mm)	Maximum Load (kg)	Inflation Pressure (kpa)
10-16.5	10	8.25	773	264	2135	520
12-16.5	12	8.25	831	307	2865	550
14-17.5	14	10.50	921	349	3875	550
15-19.5	14	11.75	1019	389	4565	485
10-16.5	10	8.25	773	264	2135	520
12-16.5	12	8.25	831	307	2865	550



QINGDAO KEBEK TIRE CO.,LTD

KEBEK®TIRE

www.chinakebektire.com

Tire patterns suitable for wheel excavator, with excellent traction capability



Wheel excavator



EXCAVATOR TIRE

Size	P.R	Rim	Overall Diameter (mm)	Section Width (mm)	Maximum Load (kg)	Inflation Pressure (kpa)
8.25-15	14	6.5	992	245	2060	675
9.00-20	14	7.0	1030	260	2500	700
10.00-20	16	7.5	1062	280	3000	750

The extra deep pattern is especially designed for loader with driving surface, unique cutting resistance, wear resistance.

It has longer service life and applicable for rough roads.



Backhoe Loader



R4

Size	P.R	Rim	Overall Diameter(mm)	Section Width (mm)	Maximum Load (kg)	Inflation Pressure (kpa)
10.5/80-18	10	9	905	274	1935	370
12.5/80-18	12	9	985	308	2625	370
16.9-24	10	W15L	1309	430	2900	220
16.9-28	10	W15L	1410	430	2380	220
17.5L-24	12	W15L	1241	445	3075	260
19.5L-24	12	DW16L	1314	495	3450	230
21L-24	12	DW18L	1378	533	3875	220



QINGDAO KEBEK TIRE CO.,LTD

KEBEK®TIRE

www.chinakebektire.com

Tyre with smooth tread pattern suitable for underground mines.



L5S



Loaders



LHD

Size	PR	Standard Rim	Tread Depth	Tyre inflated dimension (mm)		Load Capacity (kg)		Pressure (kpa)	
			(mm)	Section Width	Overall Diameter	10km/h	50km/h	10km/h	50km/h
12.00-24	24	8.50	56	315	1272	7700	4150	975	650
14.00-24	28	10.00	64	375	1370	10000	5600	925	650
17.5-25	24	14.00-1.5	63	445	1450	9200	5750	675	500
18.00-25	40	13.00-2.5	78.5	495	1671	17000	9750	950	700
20.5-25	24	17.00/2.0	71	535	1536	10300	6700	525	400
23.5-25	24	19.50/2.5	78	595	1671	12500	8000	475	355
26.5-25	28	22.00-3.0	87	675	1790	17000	11200	550	425
29.5-25	28	25.00-3.5	97.5	750	2023	23600	15000	625	475
29.5-29	40	25.00-3.5	97.5	825	2073	23600	15000	625	475

Tyre desinged for garder and loader.

Provide excellent traction and floation performance on loose soil and sand.



G2/L2



Graders

Size	PR	Standard Rim	Tread Depth	Tyre inflated dimension (mm)		Load Capacity (kg)		Pressure (kpa)	
			(mm)	Section Width	Overall Diameter	10km/h	50km/h	10km/h	50km/h
15.5-25	12	12.00/1.3	25	395	1275	4875	3000	325	225
	16	12.00/1.3	25	395	1275	5600	3250	400	250
17.5-25	16	14.00/1.5	26	445	1350	7300	4250	475	300
	20	14.00/1.5	26	445	1350	8250	5000	575	400
20.5-25	20	17.00/2.0	29	520	1490	9500	6000	450	325
	24	17.00/2.0	29	520	1490	10300	6700	525	400
1300-24	12	8.00TG	23	330	1280	5600	300	450	300
	16	8.00TG	23	330	1280	6500	3580	600	400
1400-24	12	8.00TG	26	398	1370	6300	3350	425	275
	16	8.00TG	26	398	1370	7300	4000	550	375



QINGDAO KEBEK TIRE CO.,LTD

KEBEK®TIRE

www.chinakebektire.com

Suitable to part of off-road vehicles operating on sand ground and loose road surface, with stable ride, good floating force and steering ability.



Roller




R3

Size	PR	Standard Rim	Tread Depth	Tyre inflated dimension (mm)		Load Capacity (kg)		Pressure (kpa)	
			(mm)	Section Width	Overall Diameter	30km/h		30km/h	
23.1-26	12	DW20	17	587	1605	3600		170	

Pattern has good traction, stability, anti-slip and excellent self-cleaning properties that fit in hard road and hard mining environment work.

Tyre designs suitable for bulldozers, loaders and excavators operating under many conditions.



Loaders



Dozers



E3E

Size	P.R	Standard Rim	Tread Depth	Tyre inflated dimension		Load Capacity		Pressure (kpa)	
			(mm)	Section Width	Overall Diameter	10km/h	50km/h	10km/h	50km/h
17.5-25	16	14.00-1.5	26	445	1348	7300	4250	475	300
	20	14.00-1.5	26	445	1348	8250	5000	575	400
20.5-25	20	17.00-2.0	26	521	1493	9500	6000	450	325
23.5-25	20	19.50-2.5	30	597	1617	9500	6150	375	300
	24	19.50-2.5	30	597	1617	10900	7300	475	350
26.5-25	28	22.00-3.0	35	673	1750	15500	10000	475	350



QINGDAO KEBEK TIRE CO.,LTD

KEBEK[®]TIRE

www.chinakebektire.com

APPLICATION VEHICLE MATCHING CHART

Application	Vehicle
Earthmover Service	Dump Trucks, Motor Scrapers, Articulated Dump Trucks, Coal Haulers, Logging Trucks, Other Mining Trucks, etc.
Grader Service	Motor Graders
Loader & Dozer Service	Shovels, Front-End Loaders, Back-hoe Loaders, Skid Steer Loaders, Dozers, Shuttle Trucks, Load-Haul-Dumps, etc.
High-Speed Service	All-Terrain Cranes, High-Speed Vehicles, etc.
Industrial Service	Straddle Carriers, Aircraft Towing Tractors, Container Stackers, Counter-balanced Lift Trucks, Mobile Crushers, Log Stackers, etc.
Logging Service	Log-Skidders
Compactor Service	Compactor, Road Rollers
Sand Service	Sand Service Trucks

TRA CLASSIFICATION OFF-THE-ROAD TIRES

TRA CODE	TREAD TYPE	MAXIMUM	
		SPEED	DISTANCE(ONE WAY)
E=			
E-2	Traction regular	65km/h(40mph)	4km(2.5mi.)
E-3	Rock regular	65km/h(40mph)	4km(2.5mi.)
E-4	Rock deep tread	65km/h(40mph)	4km(2.5mi.)
L=LOA			
L-2	Traction regular	10km/h(5mph)	76m(250ft.)
L-3	Rock regular	10km/h(5mph)	76m(250ft.)
L-4	Rock deep tread	10km/h(5mph)	76m(250ft.)
L-5	Rock extra deep tread	10km/h(5mph)	76m(250ft.)
L-5S	Smooth extra deep tread	10km/h(5mph)	76m(250ft.)



QINGDAO KEBEK TIRE CO.,LTD
 ADD:D&D Mansion,NO.182 Haier Road,Qingdao,China
 TEL:+86-532-88976038
 FAX:+86-532-85970970
 E-mail:manager@chinakebebtire.com
 www.chinakebebtire.com
 Exhibits:car tire,truck tire,off road tire,agricultural tire

